



Lumen



CRI



CCT



Available on request



RoHS



365°



90°



IP 20



PRODUCT INFORMATION

| LED Type | Fortimo SLM2000 G3 | | Fortimo SLM3000 G3 | | Bridgelux Vero18 3270lm | |
|----------------------|--|---------|--------------------|---------|--|---------|
| CCT | 3000K | 4000K | 3000K | 4000K | 3000K | 4000K |
| Module Power | 19W | 17.5W | 28W | 26W | max 35W | max 35W |
| Module Efficacy | 105lm/W | 114lm/W | 107lm/W | 115lm/W | 105lm/W | 111lm/W |
| System Efficacy | 91lm/W | 98lm/W | 92lm/W | 98lm/W | 93lm/W | 98lm/W |
| LOR | 84.7% | | 83.1% | | 89.5% | |
| Driver | Philips Fortimo SLM Driver Non-dimmable (included) | | | | 1050mA Tridonic Driver Non-dimmable (included) | |
| Driver Input Voltage | 230V AC | | | | | |
| CRI | >80Ra | | | | | |
| Reflector | 36° (included) | | | | 40° (included) | |

Jetzt auch erhältlich in:
Philips SLM G4+ Premium White 830
 17,1W mit 2324 lumen (Systemleistung circa 10-15% mehr)
 26,2W mit 3336 lumen (Systemleistung circa 10-15% mehr)
 33,8W mit 4014 lumen (Systemleistung circa 10-15% mehr)

OPTIONAL REFLECTORS (On Request)

| Description | |
|-------------------|---------------------------------------|
| Reflector 18° for | Philips SLM |
| Reflector 24° for | Philips SLM |
| Reflector 20° for | Bridgelux Vero18 (only for Bridgelux) |
| Reflector 30° for | Bridgelux Vero18 (only for Bridgelux) |

ACCESSORIES (inclusive)

| Description | Qty |
|-----------------------------|-----|
| LED module | 1 |
| Constant current LED driver | 1 |
| Reflector | 1 |

ACCESSORIES (On Request)

| Description |
|---|
| 3-Phase tracks and accessories |
| Dimmable driver available only on request |

